

LUNA

Apparecchio per illuminazione di esterni a una o a due uscite di luce. È disponibile in due dimensioni Ø 80 e Ø 120 e in diverse altezze costituito da:

- Base e chiusura in alluminio pressofuso verniciato
- Palo in alluminio estruso verniciato
- Diffusore in policarbonato
- Viti di chiusura in acciaio inox
- Verniciatura in polveri poliestere ad elevata resistenza ai raggi ultravioletti e alla corrosione

Outdoor luminaire with 1 or 2 light openings. Available in Ø 80 and Ø 120. Available in different heights constructed of:

- Painted die-cast aluminium base and cap
- Painted extruded aluminium post
- Polycarbonate diffuser
- Stainless steel screws
- Painting using high resistance to UV and corrosion polyester powders



Colori - Colours

X=9  Antracite
Anthracite

X=4  Silver

Diffusore - Diffuser

Codice-Code 08 2610

per/for Cod. 2610 - 2616

Codice-Code 08 2611

per/for Cod. 2611 - 2618

Codice-Code 08 2614

per/for Cod. 2614 - 2615

Codice-Code 08 2612


per/for Cod. 2612 - 2619

Le lampadine vengono fornite solo su richiesta


Bulbs supplied only on request

Classe energetica : vedi pag. 356

Energy class : see page 356



Installazione a terra
Floor mounting



LUNA MINI LED

L'apparecchio è fornito completo di alimentatore elettronico 220/240V 50/60Hz posizionato all'interno dell'apparecchio.

The luminaire is supplied with a 220/240V 50/60Hz built-in power supply.



IK 07



Per/for LUNA MINI
ACCESSORIO: art. CP 26
Supporto orientabile con picchetto in alluminio pressofuso.


Die-cast aluminium directional fixing bracket with spike.



Versione in biemissione
Double-light version




2616

**LED**


2616.66X	LED	16,8W	2x1400 lm	4000 K
-----------------	-----	-------	-----------	--------

2616.67X	LED	16,8W	2x1400 lm	3000 K
-----------------	-----	-------	-----------	--------

2616.99X		TC-L	24W	2G11
-----------------	---	------	-----	------



2618

**LED**

2618.66X	LED	16,8W	2x1400 lm	4000 K
-----------------	-----	-------	-----------	--------

2618.67X	LED	16,8W	2x1400 lm	3000 K
-----------------	-----	-------	-----------	--------

2618.98X		TC-L	18W	2G11
-----------------	---	------	-----	------