




JUMP



Faretto incasso tondo cob led, orientabile, con finitura bianca
Cob led recessed spotlight - round, adjustable, white
Spot de embutir redondo cob led, ajustável, com acabamento branco

VRD 18_05 BI 3000K
● 3000 K
350 lumen

VRD 18_05 BI 4000K
● 4000 K
370 lumen

5W  **IP20**
 

45 mm



Ø foro/hole/furo 77 mm

Ø 87 mm

finitura / finished / acabamento
voltaggio / voltage / voltagem
driver
misure / measures / medida
foro / hole / furo
angolo / beam angle / ângulo
cri
durata / life / duração
materiale / material
peso / weight

bianco / white / branco / weiß / blanc / blanco
AC 220-240V ~ 50/60 Hz
compreso / included / incluído
Ø 87 mm, H 45 mm
Ø 77 mm
60°
> 80
> 30.000 ore / hours
Alluminio + vetro / Aluminium + glass / alumínio + vidro
120 g




GEORGE


Faretto incasso tondo cob led, fisso, con finitura bianca
Cob led recessed spotlight - round, fix, white
Spot de embutir redondo com led, fixo, com acabamento branco

VRD 16_05 BI 3000K
● 3000 K
485 lumen

VRD 16_05 BI 4000K
● 4000 K
520 lumen

5W  **IP20**
 

46 mm



Ø foro/hole/furo 45 mm

Ø 55 mm


finitura / finished / acabamento
voltaggio / voltage / voltagem
driver
misure / measures / medida
foro / hole / furo
angolo / beam angle / ângulo
cri
durata / life / duração
materiale / material
peso / weight

bianco / white / branco / weiß / blanc / blanco
AC 220-240V ~ 50/60 Hz
compreso / included / incluído
Ø 55 mm, H 46 mm
Ø 45 mm
50°
> 80
> 30.000 ore / hours
alluminio / aluminium / alumínio
150 g




VRD 16_06 BI 3000K
● 3000 K
550 lumen

VRD 16_06 BI 4000K
● 4000 K
580 lumen

6W  **IP20**
 

43 mm



Ø foro/hole/furo 75 mm

Ø 90 mm

finitura / finished / acabamento
voltaggio / voltage / voltagem
driver
misure / measures / medida
foro / hole / furo
angolo / beam angle / ângulo
cri
durata / life / duração
materiale / material
peso / weight

bianco / white / branco / weiß / blanc / blanco
AC 220-240V ~ 50/60 Hz
compreso / included / incluído
Ø 90 mm, H 43 mm
Ø 75 mm
16°
> 80
> 30.000 ore / hours
alluminio / aluminium / alumínio
300 g

